

UK SockeT

Model:D1012

Technical Specification

Electrical:

Input Voltage:AC250V~50/60Hz

Rated Current: 13A per sockeT outlet

Terminal capacity: Live,neutral & earth

Cable Size:

3x2.5mm²

3x4mm²

2x6mm²

Contact gap:

3mm switch contact gap

Physical:

Operating Temperature:-5°C~50°C

IP Rated:IP20

Max Installation Altitude:≤2000M

Operational Testing:

Tested to 100,000 operations for mechanical life


Tested to 30,000 operations at 13 amp rating

Tested to 10,000 operations at 20 amp rating




Description

The British Standard Square Plug SockeT is widely used in homes, offices, shops, hotels, and other locations in the UK and related regions. It provides users with a safe and reliable power interface, allowing connection to various electrical devices such as televisions, computers, and phone chargers. Users can control the power status of their devices by plugging or unplugging the sockeT, facilitating daily use and management.




Wiring Diagram

Product Dimensions



Wiring Diagrams



Product Material

NO.	Name	Material	Specifications
1.	Surface frame	PC	SABIC GE
2.	Basebox cover	PA	
3.	Spring	Spring steels	
4.	Safeguard door	PA	Nylon
5.	Wire terminal	Brass	59 Copper particles
6.	Wire terminal	Brass	Phosphor Copper
7.	Screw	Iron	Carbon Steel
8.	Base	PA	
9.	Middle frame	Iron	

Technical characteristics

Can use in ocean weather and high temperature up to 130 celsius degree.PC material V0 flaming retarding .Strong hygroscopicity, excellent strengthand durability

Big copper connector 2.8 gram, moisture resistance and stand wear and tearDifficult to make electrical spark ,our products can use in the moist weather. 0.6mm thickness copper,moisture resistance and stand wear and tear. Difficult to make electrical spark , our products can use in the moist weathe.

4*8mm screw ,make the cable very fastness,surface gold-plating, prevent oxidation,improve the electrical conductivity

