



LED PANEL LIGHT


NR-PL102-50


IP20



Item Code	P (W)	CCT(K)	Beam angle	Output (lm)	lm/w	Hole Size (mm)	Dimensions in mm			kg
							A	B	C	
NR-PL102-50	50	4000/6500	120°	5360	107.2	□590x590	596	596	31	1.35

Dimensions in mm







Description:
LED PANEL LIGHT

Main material:
aluminium+Iron+Engineering plastics


Specification
Energy saving, up to 85% energy saving comparing to standard halogen and incandescent lamps
High quality light, high color rendering, less heat, no UV or IR radiation
LED driver is included
IP20

Applications

- . Shopping mall
- . Office buildings
- . Exhibition hall






LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



AVERAGE BEAM ANGLE (50%) : 113.4 DEG

Illuminance at a Distance






1

Turn off The Power




2

Hole: Ensure your Ceiling hole size about 590x590mm.




3

Ensure the panel light working well before installation, put the panel light at a diagonal position.




4

Put the LED driver aside and insert panel light into ceiling.




5

Rotate the panel light 45° in horizontal direction to make the front of panel face to ceiling square hole.



6

Rotate the panel light 90° in vertical direction of about 90° to make it correspond to the recessed frame and front of panel face to ground



7

Connect the cable

