




GX53 LED Ø100mm

TÜV- CB CERTIFIED LED MODULES

GX53 LED Ø100mm - CCT SETTABLE				
		POWER		10W
		LUMINOUS FLUX (Φ TOTAL)	3000 K	1190 lm
			4000 K	1290 lm
			6500 K	1210 lm
SIZE & SOCKET		 GX53		
CCT SETTABLE 3000 K 4000 K 6500 K 3000 K SILICONE PROTECTION DRIVER INDOOR & OUTDOOR USE -30 +80 °C 90% HUMIDITY VOLTAGE SURGE RESISTANT ENERGY 10 kWh/1000h COMPLY WITH: EU 2019/2015 EU 2019/2020 TUV CE CB LVD EMC ERP IECEE IECEE CB CERTIFICATE: SG PSB-LE-03887		LUMINOUS FLUX (Φ USE 120°)	975 lm	
		VOLTAGE	100-240 V	
		FREQUENCY	50/60 Hz	
		DISPLACEMENT FACTOR	>0,5	
		PSTLM (NO FLICKER)	< 1	
		SVM	0,4	
		CRI	> 80	
		SDCM	<6	
		BEAM ANGLE	112°	
		SWITCHING CYCLE	> 30.000	
		WARM UP TIME	0s	
		LIFETIME	25.000 h	
		EFFICIENCY CLASS	E	
		REF. CODE	H3.LED.G53.CCT	