

# GU10 LED - CCT SETTABLE

|                                                                                                                                                                                                                                                                                                                                                                                                                                                             |                                                                                                                                                                     |                           |                                                                                      |                |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------|--------------------------------------------------------------------------------------|----------------|
|                                                                                                                                                                                                                                                                                                                                                                            |                                                                                                                                                                     | POWER                     |                                                                                      | <b>3,5 W</b>   |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                             |                                                                                                                                                                     | LUMINOUS FLUX (Φ TOTAL)   | 2700 K                                                                               | 329 lm         |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                             |                                                                                                                                                                     |                           | 4000 K                                                                               | 366 lm         |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                             |                                                                                                                                                                     | SIZE & SOCKET             |  |                |
| <div> <p>CCT SETTABLE</p> <p>2700 K 4000 K</p> <p>500K-12</p> </div> <div> <p>SILICONE PROTECTION DRIVER</p>  <p><b>INDOOR &amp; OUTDOOR USE</b></p> <p>-30 +80 °C 90% HUMIDITY</p> <p>VOLTAGE SURGE RESISTANT</p> </div> <div> <p>ENERGY</p> <p>4</p> <p>4000h/10000h</p> <p>EUROPE</p> </div> <div> <p>COMPLY WITH:</p> <p>EU 2019/2015</p> <p>EU 2019/2020</p> </div> | <div> <p>TUV SUD</p> <p>CE LVD</p> <p>CB EMC</p> <p>ERP</p> </div> <div> <p>IECEE</p> <p>CB SCHEME</p> <p>IECEE CB CERTIFICATE:</p> <p>SG PSB-LE-02300A1</p> </div> | LUMINOUS FLUX (Φ USE 90°) |                                                                                      | 260 lm         |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                             |                                                                                                                                                                     | VOLTAGE                   |                                                                                      | 100-240 V      |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                             |                                                                                                                                                                     | FREQUENCY                 |                                                                                      | 50/60 Hz       |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                             |                                                                                                                                                                     | PSTLM (NO FLICKER)        |                                                                                      | <1             |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                             |                                                                                                                                                                     | SVM                       |                                                                                      | 0,4            |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                             |                                                                                                                                                                     | CRI                       |                                                                                      | > 80           |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                             |                                                                                                                                                                     | SDCM                      |                                                                                      | <3             |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                             |                                                                                                                                                                     | BEAM ANGLE                |                                                                                      | 43°            |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                             |                                                                                                                                                                     | SWITCHING CYCLE           |                                                                                      | > 25.000       |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                             |                                                                                                                                                                     | WARM UP TIME              |                                                                                      | ≤ 0,5"         |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                             |                                                                                                                                                                     | LIFETIME                  |                                                                                      | 25.000 h       |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                             |                                                                                                                                                                     | EFFICIENCY CLASS          |                                                                                      | F              |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                             |                                                                                                                                                                     | REF. CODE                 |                                                                                      | H.LED.GU10.CCT |